

Telehandler / Zoom Boom

Used Telehandler New Hampshire - Telehandlers go by many different names including a boom lift, telescopic handler, Cherry picker or teleporter. This industrial equipment is commonly used in a variety of industries including agriculture. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. Many different attachments can be used at the end of the articulating boom to facilitate a wide number of jobs. Common attachments include pallet forks, a winch, a bucket or a muck grab. The most common telehandler attachment is the pallet forks. They allow the operator to transport loads to and from locations that are considered unreachable with a regular forklift. Telehandlers allow cargo pallets to be loaded and unloaded from a trailer and placed on high locations such as racking or rooftops. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. It isn't always practical or affordable to rely on a crane or secondary machinery to complete the job. Within agriculture, the bucket or bucket grab is among the most popular attachments. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Having one item to complete a variety of jobs saves time, money and storage space. Telehandler machines can work in conjunction with a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. The agricultural models can use three-point linkage and power take-off to make telehandlers multi-tasking. Interestingly enough, the machines' main advantage is also its' biggest limitation. The boom raises or extends with heavy loads, acting as a lever. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. For instance, a telehandler with a five thousand pound capacity may be capable of safely lifting as little as four hundred pounds fully extended with a low boom angle with a retracted boom. This unit with a 5000 lb. lift capability and retracted boom could support as much as ten thousand pounds after the boom is raised seventy degrees. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. Updated telehandler models have computers and sensors. The operator is warned and even cut off further control input once the limits of the telehandler are surpassed. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. A mobile crane can also use a bucket is another option consisting of a stabilized rotary joint found between upper and lower frames. Compact telehandler models are available in a variety of different weights, reach, sizes and boom designs. Telehandlers fall into the compact category if the unit weighs in at 11,000 lbs. or less. A two-stage boom is a popular option for compact models whereas the three or four boom design is common for bigger machines. A low pivot boom ensures better operator visibility for transporting loads on compact units. There are narrower and smaller dimensions offered with the compact telehandler. Compact telehandlers have a reach capacity ranging between 13 to 20 feet with a lift capacity ranging from 5k to 7k pounds. These versatile machines make the compact telehandler extremely popular. This machine can be utilized for carrying tools or as a pick and place unit. This machine is often used in locations that are cramped and tight. Residential services are often employed during framing and for jobs with height restrictions. Telehandlers can enter internal building access in hard-to-reach locations. Compact units are popular in multi-story construction, nurseries, strip malls, landscaping, masonry, garage facilities and erecting steel among other applications. Telehandlers are employed by agri-business and farming applications to complete many jobs. Telehandlers can be found with two and four-wheel drive and crab steering capabilities. The unit can travel

over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. The four-wheel drive models offer the ability to traverse more difficult terrain and provide a tighter turning radius. Crab steering is responsible for the increased maneuverability, allowing the front and rear wheels to shift forty-five degrees to the right or left. Compact telehandlers have numerous cab environments to choose from. On entry-level models, there is a rollover cage for added safety. Higher-end models are equipped with a fully enclosed cab, a heater, windshield wiper and defroster. Compact units feature spacious cab accommodations to keep operators totally comfortable. Extra amenities including air conditioning, satellite radio, suspension seats, tilt steering and cup holders are available. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Ground engaging work is often completed by compact units. It is easy to enjoy the benefits of a mini excavator by adding a simple bucket attachment to the telehandler. Light-duty to heavy-duty buckets can be attached for transferring material, side-shifting and rotating fork carriages are relied on for pick and place situations, augers for drilling post holes or planting trees or pier supports, truss booms for extending reach, crane hooks, brooms for sweeping and more. Skid steer attachments are being made for versatility and other compact telehandler designs.